

MICROFABRICATED REACTOR

Inventors:

M. Allen Northrup

and

Richard M. White

RELATED APPLICATIONS

THIS

(u)

This application is related to U.S. Patent 5,129,261, Serial No. 07/467,412, ^{issued July 14, 1992} filed January 18, 1990 and application Serial No. 07/162,193, filed February 29, 1988, now abandoned, for a Plate-mode Ultrasonic Sensor. The entire disclosures of these applications are hereby incorporated by reference.

BACKGROUND OF THE INVENTION

10 The present invention relates generally to instruments for chemical reaction control, product and reactant manipulations, detection of participating reactants and resultant products, and more particularly to integrated microfabricated instruments which perform microscale chemical

15 reactions involving precise control of parameters of the reactions. The parameters of the reaction controlled by the instrument may be temperature, pressure, concentration of reactants, the intensity or frequency of incident light, electromagnetic

20 fields, or ultrasonic pressure waves, etc.

The term "integrated microfabrication" is used herein to refer to all processes used for batch production of semiconductor microelectronics, and all related microfabrication processes such as LIGA (see
5 R. S. Muller, R. T. Howe, S. D. Senturia, R. L. Smith, and R. M. White, ed. MICROSENSORS, IEEE Press, 472 pages, 1990). Microfabrication technologies include, but are not limited to, sputtering, electrodeposition, low-pressure vapor deposition,
10 photolithography and etching. Microfabricated devices are usually formed on crystalline semiconductor substrates such as silicon or gallium arsenide. Noncrystalline materials such as glass or certain polymers may be used although crystalline
15 materials provide certain advantages. The shapes of crystalline devices can be precisely controlled since etched surfaces are generally crystal planes, and crystalline materials may be bonded by processes such as fusion at elevated temperatures or the field-
20 assisted method (Mallory bonding). Materials which are not semiconductors, such as quartz or glass, may be used, though semiconductor materials provide the advantage that electronic circuitry may be integrated into the system by the use of conventional
25 integrated-circuit fabrication techniques.

Monolithic microfabrication technology now allows the production of electrical, mechanical, electromechanical, optical, chemical and thermal devices including pumps, valves, heaters, mixers and
30 species detectors for microliter to nanoliter quantities of solids, liquids and gases. Microscale sensors include optical waveguide probes and ultrasonic flexural-wave sensors. The integration of these devices into a single system allows for the
35 batch production of microscale reactor-based analytical instruments. Integrated microinstruments

may be applied to biochemical, inorganic, or organic chemical reactions to perform biomedical and environmental diagnostics, and biotechnological processing and detection.

5 Such integrated microfabricated devices can be manufactured in batch quantities with high precision, yet low cost, thereby making recyclable and/or disposable single-use devices practical. Alternatively, the instrument may consist of an array
10 of reaction instruments which are to operate in parallel to simultaneously perform a number of related reactions. Operation of such instruments is easily automated, further reducing costs. Since the analysis can be performed *in situ*, the likelihood of
15 contamination is very low. Because of the inherently small sizes of such devices, the heating and cooling can be extremely rapid, and the devices can have very low power requirements. Such devices may be powered by batteries or by electromagnetic, capacitive,
20 inductive or optical coupling.

Small volumes and high surface-area to volume ratios provide microfabricated reaction instruments with a high level of control of the parameters of a reaction. Heaters may produce
25 temperature cycling or ramping, sonochemical and sonophysical changes in conformational structures may be produced by ultrasound transducers, and polymerizations may be generated by incident optical radiation.

30 Synthesis reactions, and especially synthesis chain reactions, such as the polymerase chain reaction (PCR), are particularly well-suited for microfabricated reaction instruments. PCR can selectively amplify a single molecule of DNA (or RNA)

(as)
ins
(aw)

of an organism by a factor of 10^6 to 10^9 . This well-established procedure requires the repetition of heating (denaturing) and cooling (annealing) cycles in the presence of an original DNA target molecule, specific DNA primers, deoxynucleotide triphosphates, and DNA polymerase enzymes and cofactors. Each cycle produces a doubling of the target DNA sequence, leading to an exponential accumulation of the target sequence. PCR-based technology has been applied to a variety of analyses, including environmental and industrial contaminant identification, medical and forensic diagnostics, and biological research.

The procedure involves: (1) processing of the sample to release target DNA molecules into a crude extract; (2) addition of an aqueous solution containing enzymes, buffers, deoxyribonucleotide triphosphates (dNTPS), and oligonucleotide primers; (3) thermal cycling of the reaction mixture between two or three temperatures (e.g., 90-96, 72, and 37-55°C); and (4) detection of amplified DNA. Intermediate steps which incorporate signal-producing and/or surface-binding primers, or which purify the reaction products, via, for example, electrophoresis or chromatography may be introduced. A problem with standard PCR laboratory techniques is that the PCR reactions may be contaminated or inhibited by introduction of a single contaminant molecule of extraneous DNA, such as those from previous experiments, or other contaminants, during transfers of reagents from one vessel to another.

PCR reaction volumes are presently typically on the order of 50 microliters. A thermal cycle typically consists of heating a sample to a first temperature, maintaining the sample at the first temperature, cooling the sample to a second

lower temperature, and maintaining the temperature at that lower temperature. The rate at which the sample is heated is generally limited by the heater rather than the rate of heat transfer to the sample.

5 Presently, each of the four stages of a thermal cycle requires approximately one minute, and the time required for twenty to forty complete thermal cycles is therefore from about one to three hours. The cycling time has been reduced by performing the PCR
10 reaction in capillary tubes (see C. T. Wittwer, G. C. Fillmore, and D. J. Garling, Analytical Biochemistry, **186**, pp. 328-331 (1990)). A high-power forced air heater was used to heat the tubes. The thinnest
15 capillary tubes contained a sample volume of about ten microliters. Each cycle consisted of a heating step, a waiting period, a cooling step and another waiting period, and each step required approximately fifteen seconds.

Although the PCR reaction requires thermal
20 cycling of the reagents, any reaction that benefits from precise temperature control, and/or rapid thermal cycling, thermal ramping, or any other temperature variation of reagents with time (hereinafter to be referred to as temperature
25 programming) will be well suited for the microfabricated reaction instrument of the present invention.

An object of the present invention is therefore to provide a integrated microfabricated
30 reactor.

Another object of the present invention is to provide a reactor-based instrument for inorganic, organic and biochemical reactions, and in particular for diagnostics.

Another object of the present invention is to provide a reactor which provides high-precision control of reaction parameters.

5 Another object of the present invention is to provide a reactor which provides high-precision temperature control.

Another object of the present invention is to provide a reactor which provides rapid high-precision thermal cycling, ramping or programming.

10 Another object of the present invention is to provide a closed system reactor which is self-contained, e.g. which is shipped from the factory containing the reagents, thereby minimizing the susceptibility to contamination.

15 Another object of the present invention is to provide low-cost reaction and/or detection systems.

20 Another object of the present invention is to provide an instrument for *in situ* reactions which may be powered by incident electromagnetic radiation or batteries.

Another object of the present invention is to provide arrays of microfabricated reaction chambers which may operate in parallel or series.

25 Additional objects and advantages of the invention will be set forth in the description which follows, and in part will be obvious from the description, or may be learned by practice of the invention. The objects and advantages of the
30 invention may be realized and obtained by means of

the instrumentalities and combinations particularly pointed out in the claims.

SUMMARY OF THE INVENTION

The present invention is directed to an
5 instrument for *in situ* chemical reactions in a
microfabricated environment. The instrument is
especially advantageous for biochemical reactions
which require high-precision thermal cycling,
particularly DNA-based manipulations such as PCR,
10 since the small dimensions typical of
microinstrumentation promote rapid cycling times.

The present invention provides a reaction
instrument comprised of integrated microfabricated
elements including a reagent chamber and a means for
15 manipulating the reaction of the reagents.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are
incorporated in and constitute a part of the
specification, schematically illustrate a preferred
20 embodiment of the invention and, together with the
general description of the preferred embodiment given
below, serve to explain the principles of the
invention.

Figure 1 shows a cut-away perspective view
25 of a reaction instrument of the present invention
mounted in a power source/control apparatus.

Figure 2 is a schematic of a reaction
instrument of the present invention.

Figure 3 shows a cross-sectional view of a
30 reaction chamber of the present invention.

Figures 4(a) through 4(f) show cross-sectional views of the stages of fabrication of a reaction chamber of the present invention.

Figure 5 shows a top view of a reaction chamber (dashed outline) below the piezoelectric and ground plane layers.

Figure 6a shows the typical flow velocity profile field for a fluid forced through a conduit with static bottom and side surfaces, and Figure 6b shows the flow velocity profile for a fluid pumped through a conduit by a flexural-wave pump.

Figure 7 shows gel electrophoretic results verifying the amplification of an HIV genetic sequence in a microfabricated reaction chamber of the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENT

The microinstrument of the present invention has integrated microfabricated components that perform reactant and product manipulations and detection on microliter to picoliter samples. By the selection and integration of appropriate ^{(aa)²} microfabricated devices, a precise and reliable reaction and analysis instrument for PCR-based diagnostics is implemented.

The instrument may be fabricated in a wide variety of different forms. Many microinstruments may be manufactured on a single wafer and can run in parallel, allowing the processing and analysis of several target agents and controls simultaneously. Individual small and disposable dies, each a complete microinstrument, may be fabricated. The device may be fabricated to allow a continual flow of reagents through the instrument. A reagent reservoir of the

microinstrument may have a thin silicone rubber wall so that the reagent may be inserted into the microinstrument by a hypodermic needle.

Alternatively, a needle may be integrated into the microinstrument so that a patient can be pricked by the needle and a blood sample, or any other type of body fluid, will directly enter the instrument. An integrated needle can also be used to extract body fluids from plants and animals. The reagent may also be loaded into the microinstrument by pipetting, a modified ink-jet printing process, or other means at the factory. The reagent may be lyophilized or dried, or previously stored in the chamber.

Detection signals may be processed and stored by integrated microelectronic devices so that result interpretation and control mechanisms (which may utilize feedback) can be integrally contained on the microinstrument. The low power needs of microinstrumentation allows such systems to be powered by incident electromagnetic radiation, low voltage batteries, or incident optical radiation converted to electrical energy by on-board photocells.

The components of a microinstrument may include reservoirs for retaining reagents, agitators and mixers, heaters to perform denaturing and annealing cycles, pumps, optical and/or electromechanical sensors to discriminate reagents, and reagent separators. Microheaters may be resistive heaters consisting of materials such as polysilicon patterned onto and made an integral part of the microstructure. The micropumps may be Lamb-wave devices (see U.S. Patent No. 5,006,749, R.M. White, 1991), electrokinetic pumps, or other microfabricated pump structures. The microdetection

instruments may be fluorescence-based optical fiber spectroscopes which utilize microfabricated light sources and detectors (e.g., LEDs or diode lasers and detectors); Lamb-wave sensors (see U.S. patent 5,129,261, Serial No. 07/467,412 filed January 18, 1990, and application Serial No. 07/775,631 filed October 10, 1991); electrochemical detection of biochemical molecules by surface plasmon resonance or other processes involving immobilized biochemicals; electrochemical sensing devices; or other appropriate detection methodologies. Surface treatments may be applied to components of the device for reaction enhancement, product separation, and species detection. The surface treatments can be based on numerous well-known procedures such as silanol-based derivatizations or other appropriate treatments. Chemical species separators can utilize microelectrophoresis either in a capillary or within a gel, or can be based on other appropriate methodologies.

One embodiment of the present invention performs the polymerase chain reaction (PCR). The minute reagent volumes and the specific reaction sequence of the PCR technique play favorably into the advantages of the present invention. The integrated microsystem provides a highly automated, miniaturized, analytical instrument for very rapid *in situ* analyses and production of a variety of samples. Integrated microfabricated PCR instruments are capable of performing, *in situ*, many reactions and manipulations with precise control of temperature, evaporation, small-volume reagent delivery, product separation, isolation and detection. Such highly automated technologies should greatly expedite the use of DNA-based technologies for biomedical (e.g., the Human Genome Project); environmental (e.g.,

contaminant identification); industrial (e.g., biotechnology); and forensic applications. The principles applied and problems solved in developing a PCR instrument may of course be applied to other
5 chemical reactions, analyses, and syntheses, especially other biochemical reactions, analyses, and syntheses.

PCR in a microdevice can be just one step in a series of manipulations leading to the
10 diagnostic detection of a variety of target species or the use of PCR products in genetic engineering. Physical and chemical treatments such as those described below can also be incorporated into the pre-PCR and post-PCR phases of microdevice-based
15 treatments to augment the reactions *in situ*. Amplification via PCR yields products that may be subject to further enhancement or utilized for detection of other chemicals. Physical and chemical control via microdevices of biological cells and
20 reagents prior to and after the production of PCR products will expand the number of the potential applications of DNA-based processes and analyses.

Pre-PCR manipulation of target cells or microorganisms can be accomplished with microdevices
25 of the present invention. For example ultrasonic waves may be applied to disrupt and expose cell components through lysis, and to unravel large or long chain molecules such as DNA and proteins via disruption of secondary structure. Cell lysis may
30 also be induced electrically or chemically. Ultrasonic waves and surface chemistry treatments can be used to manipulate cells and cell-contents, as can chemical treatment by stirring and/or mixing reagents from other chambers on the microinstrument.
35 Sonication on a macro-scale in conjunction with

agitating microparticles, for example, has been used to facilitate the extraction of DNA from paraffin-embedded fixed cells (M. J. Heller, L. J. Burgart, C. J. Ten Eyck, M. E. Anderson, T. C. Greiner, and R. A. Robinson, *Biotechniques*, **11**, #3, 1991, pp. 372-377). Strategies similar to this which rely on the inherent properties of a microdevice can be used to process intact cells, microorganisms, tissues, and other analytical samples for PCR and subsequent techniques.

Potential post-PCR treatments by the microdevice are also numerous. It should be noted that PCR is often an integral part of the potential application of a device to further biotechnological manipulations and analyses. Once PCR has been performed, post-PCR manipulations can lead to a myriad of possible microdevice-based DNA analyses and treatments. A few examples of such analyses are: large-scale and small-scale DNA sequencing of target species, cell-typing, analysis of PCR products with DNA probes, DNA recombination, DNA fingerprinting, DNA cloning, cell cloning, physical mapping of genes, incorporation of genetic vectors, genetic therapy, treatment and testing of biotechnological processes, and the maintenance of DNA libraries. Such analyses can lead to the use of DNA as vectors to produce cells or other biological entities to make desired products such as proteins or other compounds, or it can be used to produce DNA for use in therapies or biotechnological processes.

PCR products may also be manipulated in order to be incorporated into genetic engineering vectors such as plasmids. The vectors may subsequently be incorporated into target cells for the production of desired compounds. The target cells or moieties and reagents can be stored in

reservoirs on the device and released for exposure to the vectors when the proper physical/chemical conditions have been established. One other potential application would be the *in situ* (*in vitro* or *in vivo*) release of PCR products for direct genetic therapy or manipulations. Direct DNA sequencing of PCR products (single or double-stranded) can be accomplished with the use of unique temperature, enzymatic, or other separation schemes and detection methodologies; all of which can be incorporated into a microdevice.

Detection windows, reflective and absorptive surfaces, optic sources and other optical components can be fabricated and integrated onto a microdevice instrument, providing optical detection capabilities. The status of a reaction may be monitored by illuminating the reagents through an optical window and measuring absorption and/or luminescence. A waveguide may be fabricated by depositing a plane of transparent material between semiconducting planes, or by bonding two wafers together, at least one of the wafers having a transparent surface layer. The optical path of the waveguide is parallel to the fabrication surface. Alternatively, a window ^{with} which an optical path parallel to the normal vector of the fabrication surface may be constructed using standard patterning techniques. Data analyses can be accomplished with on-board electronics which may provide electronic or optical output.

(ac)

Analysis of PCR products, sequences of target DNA, or synthetic analogues in microdevices can be accomplished with the manipulative capabilities of microfabricated electrical and mechanical machines. For example, two-dimensional

(un) arrays of ~~pre-determined~~ DNA sequences (probes) can be used to detect or verify PCR products, and their subsequent analyses can be accomplished with microdevices.

- (un) 5 As shown in FIG. 1, an embodiment 20 of the present invention is shown above a recess 105 in a power source/control system 100. A hypodermic ~~needle~~ ^{needle} 110 is shown inserting a sample through a silicone rubber window 120 into a reaction instrument 20.
- 10 The reaction is controlled and powered by: inductive coupling, such as that between coil L_{CL} in the instrument 20 and a magnetic coil 130 as shown in ~~FIG. 1~~ ^{FIG. 1}; by capacitive coupling, such as that between the plates of capacitor C_3 and plates 140a and 140b;
- 15 and by electromagnetic coupling between resonant circuit (not shown) in the instrument 20 and a radio-frequency antenna 135.

- A schematic of a preferred embodiment 20 of the present invention is shown in FIG. 2. Three
- 20 reagent chambers 10, 12 and 14 contain reactants. One chamber 10 contains the DNA primers, one chamber 12 contains the polymerase, and one chamber 14 contains the nucleotides and any detection-tag molecules, such as magnetic beads. The contents of
- 25 the chambers 10, 12 and 14 have been loaded at the factory. The target DNA molecule is placed in reagent chamber 10 by insertion of a hypodermic needle or the like through silicone rubber window 120. The window 120 may alternatively be composed of
- 30 any other type of appropriate natural or synthetic elastomer. The reactants in the reagent chambers 10, 12 and 14 are connected by channels 22, 24 and 26 to a reaction chamber 30. Typically the chambers 10, 12, 14 and 30 have a volume ranging from microliters
- 35 to nanoliters. The channels 22, 24 and 26 are

equipped with Lamb-wave pumps LW_1 , LW_2 and LW_3 , respectively, for pumping the reactants in the reactant chambers 10, 12 and 14 in the directions of the arrows to the reaction chamber 30. The Lamb-wave pumps may be located on any wall, or on multiple walls, of the channels 22, 24 and 26. Lamb-wave pump LW_1 is connected to a capacitor C_1 . Similarly the other two Lamb-wave pumps LW_2 and LW_3 are connected to capacitors C_2 and C_3 , respectively.

10 The surface tension across the narrow midsections of the channels 22, 24 and 26 prevents the reactants from flowing into the reaction chamber 30 until pumping is initiated. The surfaces of the channels 22, 24 and 26 may be treated to raise the
15 surface tension thereby further inhibiting flow of reagents when the pumps LW_1 , LW_2 and LW_3 are not activated.

 The reaction chamber 30 may be equipped with a Lamb-wave transducer LW_C and a heater H_C . The
20 Lamb-wave transducer is connected to inductor L_{CL} . The heater H_C is connected to a resonant circuit consisting of an inductor L_{CH} and a capacitor C_{CH} . The Lamb-wave transducer LW_C acts as an agitator, mixer, or sonochemical inducer.

(LW) A channel 32 connects the reaction chamber 30 to a detection chamber 34. The channel ~~32~~³⁴ is equipped with a Lamb-wave pump LW_{DP} , which is connected to a resonant circuit consisting of an inductor L_{DP} and a capacitor C_{DP} . The detection
30 chamber 34 is equipped with a Lamb-wave sensor LW_D . The Lamb-wave sensor LW_D is connected to a capacitor C_D .

For ease of notation, an exemplary Lamb-wave device chosen from the set LW_1 , LW_2 , LW_3 , LW_C , LW_{DP} , and LW_D will be denoted by LW and the corresponding capacitor and/or inductor electrically connected to the Lamb-wave device will be denoted by C and L , respectively, hereinafter. Lamb-wave transducers have high mechanical Q values and can therefore be powered by only a narrow range of alternating voltage frequencies. The Lamb-wave pumps LW_1 , LW_2 , and LW_3 , and the Lamb-wave sensor LW_D are powered capacitively by generating an electric field between the plates 140a and 140b at the resonant frequencies of the Lamb-wave transducers LW_1 , LW_2 , LW_3 , and LW_D . The alternating frequency electric fields generate alternating frequency voltages across the capacitors C_1 , C_2 , C_3 and C_D , and Lamb waves at this frequency in the transducers LW_1 , LW_2 , LW_3 and LW_D . But because the transducers LW_1 , LW_2 , LW_3 , and LW_D have high Q values, only when the frequency of the imposed field is near the resonant frequency of a transducer does the transducer vibrate with any substantial magnitude. Similarly, the Lamb-wave mixing chamber transducer LW_C is powered by an alternating frequency magnetic field generated by the coil 130 at the mechanical resonant frequency of the transducer LW_C . The heater H_C and the Lamb-wave pump LW_{DP} are activated by directing an electromagnetic wave from the antenna 135 to the resonant circuits C_{CH} and L_{CH} , and C_{DP} and L_{DP} , respectively. The frequency of the incident electromagnetic radiation must correspond to the resonant frequency of the electrical elements C_{DP} , L_{DP} and LW_{DP} , and must also correspond to the mechanical resonant frequency of the transducer LW_{DP} , to activate the pump LW_{DP} . The frequency of the incident electromagnetic radiation must correspond to the resonant frequency of the

electrical elements C_H , L_{CH} and H_C to activate the heater H_C .

The PCR reaction is initiated by pumping the reagents in the reagent chambers 10, 12 and 14 along the directions of the arrows to the reaction chamber 30 by activating the reagent pumps LW_1 , LW_2 and LW_3 . A series of approximately twenty to forty thermal cycles are then initiated, during each cycle the temperature of the reactants in the reaction chamber 30 goes from 55°C to 96°C, and back to 55°C, for example. The temperature of the reaction chamber 30 is determined by the power of the incident electromagnetic signal at the frequency corresponding to the resonant frequency of the circuit comprised of the capacitor C_{CH} , and the inductor L_{CH} , together with the heater H_C . The reaction chamber 30 Lamb-wave device LW_C acts as an agitator or mixer as described below to mix the reagents and promote the reaction.

When the thermal cycling is complete the contents of the reaction chamber 30 are pumped by Lamb-wave pump LW_{DP} in the direction of the arrow to the detection chamber 34. The preferred embodiment utilizes a Lamb-wave sensor LW_D . Alternatively, the detection chamber may be provided with an optical window and testing may be performed by fluorescence-based or absorption-based optical spectroscopy.

A cross-sectional view taken along line 3-3 of FIG. 2 of the reaction chamber 30 is shown in FIG. 3. FIGS. 4(a)-(f) show cross-sectional views of the bottom half of the chamber during successive stages of formation of the chamber 30 from a silicon substrate 50b. A similar set of stages are involved in the fabrication of the top portion of the chamber

30. Once fabricated, the top and bottom portions may be bonded together by Mallory bonding.

The chamber cavity 31 is bounded by a ceiling 70t, a floor 70b, and side walls consisting of silicon sections 50t and 50b and silicon nitride sections 49tl, 49bl, 49tr and 49br. The height of the chamber cavity 31 is approximately 0.5 mm, and the width and length of the chamber are approximately 4 mm or less. The whole instrument 20 may fit on a wafer as small as 1 cm x 1 cm x 0.5 cm.

The indentations in the silicon substrates 50b and 50t are formed by coating one side of the substrates 50b and 50t with silicon nitride layers 52b and 52t, and patterning silicon nitride layers on the other sides of the substrates 50b and 50t to form sections 49bl, 49br, 49tl, and 49tr, respectively, as shown in FIGS. 3 and 4(a). The silicon-nitride layers 52t and 52b are preferably applied by low-pressure chemical-vapor deposition of the silicon-nitride, and are preferably a low-stress nitride. The thickness of silicon-nitride layers 52t and 52b is chosen to provide a balance between the mechanical strength of the layers which increases with thickness, and the sensitivity of the Lamb-wave detector which decreases with thickness. The thickness is also chosen to provide practical resonant frequencies for the device. The thickness of the silicon-nitride layers 52t and 52b is preferably about 3 μm , plus or minus ten percent.

30 The system is etched, for example with the wet chemical etchant KOH, to create a cavity in the silicon substrate 50 as shown in FIG. 4(b). The remaining sections of silicon ^{50b}~~50b1 and 50b2~~ form portions of the side walls of the cavity 31.

(end)

(u) Located outside the reaction chamber cavity
31 to the exterior of ^{silicon-}nitride layers 52b and 52t are
top and bottom polycrystalline silicon layers 54t and
54b, respectively. The polycrystalline layers 54t
(u) 5 and 54b are deposited on the ^{silicon-}nitride layers 52b and
52t by chemical vapor deposition and selectively
patterned. The bottom portion of the chamber 30 with
the patterned polycrystalline layer 54b on the
silicon nitride layer 52b is shown in FIG. 4(c). The
10 thickness of the polycrystalline layers 54t and 54b
is preferably between 2000 and 4000 angstroms, and
more preferably 3000 angstroms, plus or minus five
percent.

(u) Top and bottom barrier layers, composed of
15 an insulating material such as low-stress silicon
nitride or silicon dioxide, are deposited by low-
temperature oxidation and patterned. The lower
barrier layers 58bl, 58bcl, 58bc, 58bcr and 58br lie
to the exterior of the polycrystalline layer 54b and
20 the ^{silicon-}nitride layer 52b as shown in FIG. 4(d).
Similarly, the upper barrier layers 58tl, 58tcl,
58tc, 58tcr, and 58tr lie to the exterior of the
polycrystalline layer 54t and the ^{silicon-}nitride layer 52t.
(u) ~~Left and right top access holes 64tl, 64tr, 65tl, and~~
25 ~~65tr provide access to the polycrystalline layer 54t.~~
~~Similarly, left and right bottom access holes 64bl,~~
~~64br, 65bl, and 65br provide access to the bottom~~
~~polycrystalline layer 54b.~~ (u)³ The thickness of the
30 barrier layers 58tl, 58tcl, 58tc, 58tcr, and 58tr,
(to be collectively referred to as 58t) and 58bl,
58bcl, 58bc, 58bcr and 58br (to be collectively
referred to as 58b) is preferably between 1000 and
5000 angstroms, and more preferably 2500 angstroms,
plus or minus ten percent. The ^{silicon-}nitride layers 52b
(u) 35 and 52t and the barrier layers 58b and 58t thermally

C isolate the polycrystalline layers 54b and 54t from
the high conductivity silicon layers ~~50bl, 50br, 50tl~~^{50b and 50t}
C ~~and 50tr~~, thereby increasing the effectiveness of the
heaters formed by the polycrystalline layers 54b and
5 54t.

As shown in FIGS. 3 and 4(e), top left and
right conducting leads 56tl and 56tr, bottom left and
right conducting leads 56bl and 56br, top left and
right transducers 60tl and 60tr, bottom left and
10 right transducers 60bl and 60br, top left and right
four-contact resistance monitoring leads 67tl and
67tr, and bottom left and right four-contact
resistance monitoring leads 67bl and 67br are then
patterned onto the device. Through access holes 64tl
15 and 64tr, the leads 56tl and 56tr make electrical
contact with the polycrystalline layer 54t, and
similarly for the bottom section of the chamber 30.
Through access holes 65tl and ~~65tr~~^{65t}, the leads 67tl
and 67tr make electrical contact with the
20 polycrystalline layer 54t, and similarly for the
bottom section of the chamber 30. The top
polycrystalline layer 54t is therefore electrically
connected to leads 56tl, 56tr, 67tl and 67tr.
Similarly, the bottom polycrystalline layer 54b is
25 electrically connected to lead 56bl, 56br, 67bl and
67br. Current passing through polycrystalline layers
54t and 54b generates heat. Therefore, the
temperature of the chamber 30 can be controlled by
the amount of voltage applied across the top and
30 bottom leads 56tl and 56tr, and 56bl and 56br,
respectively. Because the exterior temperature is
generally below that of the chemical reactions the
system is cooled by the ambient air and cooling
elements are not generally required.

vis
(un) 4

The temperature of the system is monitored by measurement of the resistance of the polycrystalline layers 54t and 54b by connecting leads 67tl and 67tr, and 67bl and 67br of four-contact resistance measuring circuits (not shown) to the top and bottom polycrystalline layers 54t and 54b, respectively. The resistance increases linearly with temperature.

(u) FIG. 5 depicts a view of the bottom of the chamber 30 subsequent to the deposition of the transducers 60bl and 60br, leads 56bl and 56br, and four-contact resistance leads 67bl and 67br, as shown in FIG. 4(e). For clarity not all transducer leads 64blx, 64bly, 64brx and 64bry shown in FIG. 5 are depicted in FIGS. 3, 4(e) and 4(f). Only six fingers per transducer ~~60tl~~^{60tl} and ~~60tr~~^{60tr} are shown in FIGS. 5 for clarity, though transducers having approximately twenty or more fingers are preferred. The cavity 31 and channels 24 and 32 lay beneath the barrier layer 58b in the region between the dashed lines 29 and the crossbars of the T-shaped leads 56bl and 56br. The access holes 64bl and 64br (not shown in FIG. 5) lie beneath the cross-bars of the leads 56bl and 56br, and the access holes 65bl and 65br (not shown in FIG. 5) lie beneath the cross-bars of the leads 67bl and 67br, respectively. The bottom left Lamb-wave transducer 60bl consists of a plurality of interlaced fingers which are electrically connected to a pair of transducer leads 64blx and 64bly. The top left and right transducers 60tl and 60tr and the bottom left and right transducers 60bl and 60br have similar shapes. The bottom transducers 60bl and 60br and the bottom transducer leads 64bly, 64blx, 64bry and 64brx, and the leads 56bl, 56br, 67bl and 67br are aluminum and have a thickness of preferably 2000 to 6000 angstroms, and more preferably a thickness of

4000 angstroms, plus or minus ten percent. The bottom transducers 60bl and 60br and leads 56bl, 56br, 67bl, and 67br may be alternatively be made of low-temperature oxide, or any other appropriate
5 conducting material. The top transducers 60tl and 60tr and leads 56tl, 56tr, 67tl, and 67tr may be similarly constructed.

As shown in FIGS. 3 and 4(f), a bottom piezoelectric layer 62b extending between and
10 covering leads 67bl and 67br, fingers of the bottom transducers 60bl and 60br, and portions of leads 56bl and 56br is then deposited and patterned. Similarly, a top piezoelectric layer 62t extending between and
15 covering leads 67tl and 67tr, fingers of the bottom transducers 60tl and 60tr, and portions of leads 56tl and 56tr is then deposited and patterned. The piezoelectric material may be ZnO or any other appropriate material. The thickness of the piezoelectric sections 62t and 62b is preferably
20 between 0.5 and 2.0 μm , more preferably 1 μm , plus or minus ten percent.

The piezoelectric sections 62t and 62b are covered by top and bottom conducting ground planes 66t and 66b, respectively, as shown in FIGS. 3 and
25 4(f). The ground planes 66t and 66b may be aluminum, or any other appropriate conducting material. The thickness of the conducting ground plane layers 66t and 66b is preferably between 2000 and 6000 angstroms, and more preferably 4000 angstroms, plus
30 or minus ten percent.

Lamb waves, also known as plate-mode waves, have a compressional component and a shear component. Together the components of a traveling Lamb-wave in a slab can transport liquids and gases adjacent the

slab, much the same way ocean waves transport a surfing board. Lamb-wave devices can therefore act as pumps. Material near the surface of the slab has the maximum velocity since there are essentially no
5 boundary layer effects. This is extremely advantageous for the small geometries associated with microdevices. FIG. 6a shows the typical flow velocity of a fluid through a conduit with two planar walls to illustrate the effect of the friction
10 induced by walls on the flow. The velocity profile is parabolic, and at the left and right edges of the conduit the velocity drops to zero due to friction between the fluid and the walls. The friction between the walls and the fluid reduces the
15 efficiency of the pumping. In contrast, FIG. 6b shows the flow velocity of a fluid through the same conduit when the front and back walls are Lamb-wave pumps. The flow velocity is almost constant between the right and left walls. The viscosity of the fluid
20 transmits the momentum of the fluid near the Lamb-wave pumps to the fluid farther from the pumps.

Lamb waves require a propagation medium which is at most several wavelengths thick. The Lamb waves in this invention have frequencies in the
25 approximate range of 1 to 200 MHz, and typical pumping velocities for a Lamb-wave device operated with a 10 volt transducer voltage are 300 $\mu\text{m}/\text{sec}$ for water, and 2 cm/sec for air.

The layers 54t, 58t, 62t and 66t which
30 border the top of the chamber cavity 31 will hereinafter be referred to as the ceiling 70t of the chamber 30, and the layers 54b, 58b, 62b and 66b which border the bottom of the chamber cavity 31 will hereinafter be referred to as the floor 70b of the
35 chamber 30. Lamb waves are generated in the ceiling

(a) C
(a) C
C
(a) C
70t of the chamber 30 by applying an alternating voltage between a transducer lead, for instance the upper left lead ^{b4bl}~~64tl~~ of F 3. 5, and the ^{bottom}~~top~~ ground plane ^{b6br}~~66t~~. The transducer electrodes ^{b6tl}~~60tl~~ ^{b2b}~~60tl~~ 5 differentially deform the piezoelectric material ^{70b}~~62t~~ to produce a mechanical wave motion in the ceiling ^{70b}~~70t~~. The amplitude of the Lamb waves is increased by applying a second alternating voltage which is 180° out of phase to the transducer lead ^{b4br}~~64tl~~ connected 10 to the set of interlaced fingers.

Traveling waves are generated in the Lamb-wave pumps LW₁, LW₂, LW₃, and LW_{DP} in the directions of the arrows of FIG. 2 by application of alternating voltages to the pumps LW₁, LW₂, LW₃, and LW_{DP} at the 15 arrow-tail side. Standing waves are generated in the Lamb-wave detector LW_D by application of in-phase alternating voltages electrodes at both sides of the chamber. By sending Lamb-waves from left to right across the ceiling 70t of the mixing chamber 30 (by 20 application of an alternating voltage between top left transducer 60tl and the top ground plate 66t) and Lamb waves from right to left across the floor 70b of the chamber 30 (by application of an alternating voltage between bottom right transducer 25 60br and the bottom ground plate 66b), a stirring or circulating action can be produced.

The phenomenon responsible for the operation of the Lamb-wave sensor LW_D in the detection chamber 34 is elastic wave propagation 30 along a medium whose characteristics can be altered by a measurand, such as viscosity or density of the ambient fluid or gas. Where the characteristics of the waves propagating along the medium are dependent upon the characteristics of the propagation medium, 35 the wave characteristics can be monitored or measured

to provide an indication of the measurand value. For example, when the device absorbs vapors or gases from the atmosphere in a film deposited on the surface, the output frequency changes. Tests and analysis
5 indicate that Lamb-wave sensors are at least an order of magnitude more sensitive than other types of acoustical vapor sensors operating at the same wavelength. The type of DNA in an ambient fluid can be determined by measuring the viscosity as a
10 function of temperature, since the denaturing temperatures of different types of DNA are well known.

Since Lamb-wave sensors can operate while in contact with a liquid such as water, their use as
15 biosensors is very significant. For instance, the surface of a Lamb-wave sensor may be coated with single strands of a particular DNA molecule. If the device is immersed in a solution containing that same type of DNA molecule, the molecules in solution will
20 pair with the molecules on the surface, increasing the mass of the membrane and therefore decreasing the frequency of oscillation. Also, the membrane may be made of a porous and permeable material, allowing the coating of a greater surface area and also allowing
25 the liquid to be flowed through the membrane, in order to speed up the DNA attachment. Intercalating dyes, such as ethidium bromide, may be used to augment viscosity changes which occur during a reaction, thereby increasing the sensitivity of the
30 sensor. Other biological interactions may also be sensed.

Figure 7 shows gel electrophoresis results verifying the amplification of a specific HIV nucleic acid sequence performed by the microfabricated
35 reaction instrument of the present invention. The

two outside bands C_1 and C_2 represent calibrating size standards, and the three bands labelled as D_1 represent the DNA amplified in the microreactor. The two bands E_1 to the left of center are results
5 obtained with a commercial PCR thermocycler instrument from the same reaction mixture as that in the microreactor. Since bands E_1 and D_1 are at the same height it is indicated that the microreactor has produced the correct target. The thermal cycles of
10 the commercial instrument were 4 minutes long. Those of the microreactor of the present invention were 1 minute in length.

In summary, an apparatus and method for *in situ* chemical reactions in a microfabricated
15 instrument has been described. It has been shown that the instrument facilitates extremely rapid thermal cycling and high-precision temperature control of microliter to nanoliter volumes. The apparatus and method are well suited for DNA-based
20 reactions, such as PCR. It has also been shown that such integrated devices minimize the possibility for contamination of the reactions and may be operated at a distance by electromagnetic fields.

The present invention has been described in
25 terms of a preferred embodiment. However, the invention is not limited to the embodiment depicted and described. Many variations within the scope of the present invention are possible. For instance, the instrument may consist of a series of chambers at
30 different temperatures, and the temperature programming of the reagents may be accomplished by transport of the reagents through the series of chambers. The instrument may have an input channel and an output channel, and may be adapted to provide
35 a continual flow-through synthesis. Thermal cycling

may be accomplished by repeated transfer of reagents between two or more chambers which are heated to different temperatures.

In another alternate embodiment the
5 monitoring of the temperature of a chamber is accomplished at a distance by connecting an LC circuit to a probe across a polycrystalline heating layer and measuring the Q-factor of the circuit. The Q-factor is measured by exciting the circuit with an
10 incident electromagnetic field at the resonant frequency of the circuit and monitoring the time decay of the resonance, or by measuring the bandwidth of the circuit by applying a frequency modulated incident EM field and measuring the circuit's
15 frequency response. Since the measured Q-factor is inversely proportional to the resistance and the resistance increases linearly with temperature, the temperature may be determined by the measured Q-factor.

20 Other possible variations within the spirit of the invention include: the dimensions of components of the instrument are not limited to those disclosed; more or fewer reactants may be used and the reactants may be ^{such as a protein} organic, inorganic, or a
25 combination of organic and inorganic; the detection means may be located in the same chamber ^{as} as the mixing means; components of the device may be made of semiconducting materials other than silicon, or of quartz, glass, polymers or other materials; the
30 microfabricated instrument may be formed by the bonding of two wafers; the instrument may be provided with optical windows for optical monitoring of the reaction; the instrument may be controlled by direct electrical coupling of control circuitry to
35 the leads of the pumps, heater and sensor; a

(66)
in
(a)
is
(a) b

silicone-rubber window may form a penetrable wall of any chamber or channel; the instrument may be fabricated from a silicon-based material; the instrument may be powered by an integrated

- 5 microfabricated battery; any Lamb-wave transducer may be activated by capacitive, inductive, electromagnetic or optical means; or electrokinetic pumps, or any other appropriate type of pumping means, may be substituted for the Lamb-wave pumps.

- 10 Accordingly, the scope of the invention is defined by the appended claims.